


		产品技术规格书 Product Technical Specification		文件编号/ Document Number: NYTZ/YF-JSGGS-263-2025 版本号/Version: A/0 页数/Page: 1/1
型号/Type	WDZCN-YJY23		电压等级/ voltage	0.6/1kV
规格/Specification	4x240mm ²		参考标准/ standard	GB/T12706.1-2020
产品结构图 Product Structure Diagram				
	1.导体(Conductor) 2.绝缘(Isolation) 3.填充(Filling material) 4.包带(Cable wrapping) 5.铠装(Armor)6.外护套(Outer sheath)			
线缆结构/Cable structure				
芯数×截面/Core×Section			4x240mm ²	
导体/Conductor	材质/Material		裸铜丝/Bare copper wire	
	类型/Type		2 类铜导体/Class 2 copper conductor	
	参考外径/Reference outer diameter (mm)		18.2	
耐火层/Fireproof layer	材质/Material		云母带 (Muscovite belt)	
导体屏蔽 /Conductor shielding	材质/Material		/	
	标称厚度/Nominal thickness (mm)		/	
绝缘/Isolation	材质/Material		90°C交联聚乙烯绝缘料 90°C cross-linked polyethylene insulation material	
	标称厚度/Nominal thickness (mm)		1.7	
	最薄点/thinnest point (mm)		1.43	
	颜色/Colour		依客户要求/At customer's request	
绝缘屏蔽/Insulation shielding	材质/Material		/	
	标称厚度/Nominal thickness (mm)		/	
包带/Tape	材质/Material		非吸湿性包带/Non hygroscopic straps	
填充/Fill	材质/Material		非吸湿性填充/Non hygroscopic filling	
金属屏蔽 Metal shielding	材质/Material		/	
铠装/Armor	材质/Material		镀锌钢带铠装/Galvanized steel strip armor	
外护套 Outer sheath	材质/Material		90°C无卤低烟阻燃聚烯烃护套料/90°C halogen-free low-smoke flame-retardant polyolefin sheath material	
	标称厚度/Nominal thickness (mm)		2.9	
	最薄点/Thinnest point (mm)		2.12	
	颜色/Colour		依客户要求/At customer's request	
成品最大外径/Maximum finished outer diameter (mm)			66.0	
印字信息/Printing Information			Shanghai Nanyang Cable Co., Ltd WDZCN-YJY23 0.6/1kV 4x240mm ² ****m	
电气性能/Electrical performance				
耐电压/Withstanding voltage			3.5kV/5min	
导体最高正常运行温度/Max. normal operating temperature of conductor			90°C	
环境温度/Ambient temperature			-15°C~90°C	
编制/日期 Prepared by/Date		审核/日期 Checked by/Date		批准/日期 Approved by/Date
丁兴兵 22025.11.27		杨振锋 2025.11.27		史军涛 2025.11.27